

SECTION 1: IDENTIFICATION**Product Identifier****Product Name:** EJ-290 Part A Resin & Part B Monomer**Product Form:** Mixture, Article**Intended Use of the Product**

Radiation detection applications.

Name, Address, and Telephone of the Responsible Party

Company/Manufacturer: Eljen Technology
Address: 1300 W. Broadway
SWEETWATER, TEXAS 79556
USA
Phone: (325) 235-4276
Fax: (325) 235-0701
Website: www.eljentechnology.com

Emergency Telephone Number

Emergency Number: CHEMTREC (24 hours)
(800) 424-9300

SECTION 2: HAZARDS IDENTIFICATION**Classification of the Substance or Mixture****Classification (GHS-US):**

Flammable Liquid, Category 3	H226
Acute Toxicity, Inhalation, Category 4	H332
Skin Irritation, Category 2	H315
Eye Irritation, Category 2A	H319
Aspiration Hazard, Category 1	H304
Acute Aquatic Toxicity, Category 3	H402
Chronic Aquatic Toxicity, Category 2	H411

Label Elements**GHS-US Labeling:****Hazard Pictograms (GHS-US):****Signal Word (GHS-US):** Danger**Hazard Statements (GHS-US):**

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H402	Harmful to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

EJ-290 Part A Resin & Part B Monomer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Precautionary Statements (GHS-US):

P210	Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapors, mist, or spray.
P264	Wash hands, forearms, and other exposed areas thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing, and eye protection.
P301+P310	IF SWALLOWED: Immediately call a poison center or doctor.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a poison center or doctor if you feel unwell.
P321	Specific treatment (see section 4 on SDS).
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370+P378	In case of fire: Use appropriate media (see section 5) to extinguish.
P391	Collect spillage.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with all local, regional, national, provincial, territorial and international regulations.

Hazards Not Otherwise Classified

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. This material or its emissions may defat skin. This product has been stabilized with Butylated hydroxytoluene. Product will not undergo hazardous polymerization when stored under normal conditions. Vinyl toluene, if not stabilized or under extreme heat, will polymerize with generation of heat. Uninhibited monomer vapors can polymerize and plug ventilation and relief devices causing dangerous pressure and vapor concentrations to build. Substance is a strong reducing agent and reacts violently with oxidants and aluminum salts.

Components With Unknown Acute Toxicity (GHS-US)

Not applicable.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Hazardous Components:

Any hazardous components not listed below are not present in quantities requiring disclosure.

Name	Product Identifier	Concentration (%)	Classification (GHS-US)
Vinyl Toluene	CAS# 25013-15-4	95 – 100	Flam. Liq. 3, H226; Acute Tox. 4 (Inhalation: vapor), H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Asp. Tox. 1, H304; Aquatic Acute 3, H402; Aquatic Chronic 2, H411
2,5-Diphenyloxazole	CAS# 92-71-7	1 – 5	Acute Tox. 4 (Oral), H302; Eye Irrit. 2A, H319; Aquatic Chronic 4, H413

EJ-290 Part A Resin & Part B Monomer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

1,4-Bis(5-phenyl-2-oxazole)benzene	CAS# 1806-34-4	< 1	Acute Tox. 4 (Oral), H302; Eye Irrit. 2A, H319
2,6-Dit-tert-butyl-p-cresol	CAS# 97123-41-6	< 1	Aquatic Acute 1, H400; Aquatic Chronic 1, H410

For full text of H-phrases, see section 16.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Seek medical attention.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: DO NOT INDUCE VOMITING. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Small amounts of material which enter the mouth should be rinsed out until the taste is dissipated.

Most Important Symptoms and Effects, Both Acute and Delayed

Inhalation: Harmful if inhaled. High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Skin Contact: Causes skin irritation. May be absorbed through the skin in harmful amounts.

Eye Contact: Causes serious eye irritation.

Ingestion: May be fatal if swallowed and enters airways. Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None known.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If any of the above symptoms are present and persist, seek immediate medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Agents: Dry powder, alcohol-resistant foam, water in large amounts, carbon dioxide (CO₂). Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising from the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable/explosive vapor-air mixture.

Reactivity: This product has been stabilized with Butylated hydroxytoluene. Product will not undergo hazardous polymerization when stored under normal conditions. Vinyl toluene, if not stabilized or under extreme heat, will polymerize with generation of heat.

EJ-290 Part A Resin & Part B Monomer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Uninhibited monomer vapors can polymerize and plug ventilation and relief devices causing dangerous pressure and vapor concentrations to build. Substance is a strong reducing agent and reacts violently with oxidants and aluminum salts.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting instructions: Keep upwind. Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not allow run-off from firefighting to enter drains or water courses. Do not breathe fumes from fires or vapors from decomposition.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Black smoke.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat, sparks, open flames, hot surfaces. No smoking. Handle in accordance with good industrial hygiene and safety practice.

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Ventilate area. Eliminate ignition sources. Evacuate unnecessary personnel. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Eliminate all ignition sources. Use only non-sparking tools. Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container for disposal. Do not take up in combustible material such as saw dust or cellulosic material. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered. Contact competent authorities after a spill.

Reference to Other Sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Contaminated work clothing should not be allowed out of the workplace. Wash hands and forearms thoroughly after handling.

EJ-290 Part A Resin & Part B Monomer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, lighting, ventilating equipment. Air space/oxygen above the product is vital to keep inhibitors active.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store locked up. Keep in fireproof place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Aluminum chloride. Peroxides.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or appropriate advisory agency.

Components with Workplace Control Parameters:

Vinyl Toluene (CAS# 25013-15-4)		
Mexico	OEL TWA (mg/m ³)	240 mg/m ³
Mexico	OEL TWA (ppm)	50 ppm
Mexico	OEL STEL (mg/m ³)	485 mg/m ³
Mexico	OEL STEL (ppm)	100 ppm
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA ACGIH	ACGIH STEL (ppm)	100 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	480 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	480 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA IDLH	US IDLH (ppm)	400 ppm
Alberta	OEL STEL (mg/m ³)	483 mg/m ³
Alberta	OEL STEL (ppm)	100 ppm
Alberta	OEL TWA (mg/m ³)	242 mg/m ³
Alberta	OEL TWA (ppm)	50 ppm
British Columbia	OEL STEL (ppm)	75 ppm
British Columbia	OEL TWA (ppm)	25 ppm
Manitoba	OEL STEL (ppm)	100 ppm
Manitoba	OEL TWA (ppm)	50 ppm
New Brunswick	OEL STEL (mg/m ³)	483 mg/m ³
New Brunswick	OEL STEL (ppm)	100 ppm
New Brunswick	OEL TWA (mg/m ³)	242 mg/m ³
New Brunswick	OEL TWA (ppm)	50 ppm
Newfoundland & Labrador	OEL STEL (ppm)	100 ppm
Newfoundland & Labrador	OEL TWA (ppm)	50 ppm
Nova Scotia	OEL STEL (ppm)	100 ppm
Nova Scotia	OEL TWA (ppm)	50 ppm
Nunavut	OEL STEL (mg/m ³)	483 mg/m ³

EJ-290 Part A Resin & Part B Monomer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Nunavut	OEL STEL (ppm)	100 ppm
Nunavut	OEL TWA (mg/m ³)	242 mg/m ³
Nunavut	OEL TWA (ppm)	50 ppm
Northwest Territories	OEL STEL (mg/m ³)	483 mg/m ³
Northwest Territories	OEL STEL (ppm)	100 ppm
Northwest Territories	OEL TWA (mg/m ³)	242 mg/m ³
Northwest Territories	OEL TWA (ppm)	50 ppm
Ontario	OEL STEL (ppm)	100 ppm
Ontario	OEL TWA (ppm)	50 ppm
Prince Edward Island	OEL STEL (ppm)	100 ppm
Prince Edward Island	OEL TWA (ppm)	50 ppm
Québec	VECD (mg/m ³)	483 mg/m ³
Québec	VECD (ppm)	100 ppm
Québec	VEMP (mg/m ³)	242 mg/m ³
Québec	VEMP (ppm)	50 ppm
Saskatchewan	OEL STEL (ppm)	100 ppm
Saskatchewan	OEL TWA (ppm)	50 ppm
Yukon	OEL STEL (mg/m ³)	720 mg/m ³
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m ³)	480 mg/m ³
Yukon	OEL TWA (ppm)	100 ppm

2,6-Di-tert-butyl-p-cresol (97123-41-6)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (inhalable fraction and vapor)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	2 mg/m ³ (aerosol, inhalable, and vapor)
Manitoba	OEL TWA (mg/m ³)	2 mg/m ³ (inhalable fraction and vapor)
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	2 mg/m ³ (inhalable fraction and vapor)
Nova Scotia	OEL TWA (mg/m ³)	2 mg/m ³ (inhalable fraction and vapor)
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³
Ontario	OEL TWA (mg/m ³)	2 mg/m ³ (inhalable fraction and vapor)
Prince Edward Island	OEL TWA (mg/m ³)	2 mg/m ³ (inhalable fraction and vapor)
Québec	VECD (mg/m ³)	10 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	4 mg/m ³ (inhalable fraction and vapor)

EJ-290 Part A Resin & Part B Monomer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Saskatchewan	OEL TWA (mg/m ³)	2 mg/m ³ (inhalable fraction and vapor)
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	10 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Gas detectors should be used when flammable gases/vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Ensure all national/local regulations are observed.

Personal Protective Equipment

Eye/Face Protection: Wear chemical safety goggles.

Skin and Body Protection: Wear chemically resistant protective gloves. Wear suitable protective clothing made from chemically and fire resistant/ flame retardant materials and fabrics.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Appearance	: Viscous, clear, blue, fluorescent liquid
Odor	: Aromatic
Odor Threshold	: No data available
pH	: No data available
Melting Point	: No data available
Boiling Point/Boiling Range	: 168 °C (334 °F)
Flash Point	: 53 °C (127 °F)
Evaporation Rate	: Very slow
Flammability (solid, gas)	: No data available
Lower Flammability/Explosion Limit	: 5.3%
Upper Flammability/Explosion Limit	: 1.1%
Vapor Pressure	: 1.1 mm at 20 °C (68 °F)
Vapor Density	: 4.1 at 20 °C (68 °F)
Relative Density	: No data available
Solubility	: Nil in water
Partition Coefficient (n-octanal/water)	: No data available
Auto-Ignition Temperature	: 515 °C (959 °F)
Decomposition Temperature	: No data available
Viscosity	: No data available
Percent Volatile by Volume	: 100%
Explosion Data – Sensitivity to Mechanical Impact	: Not expect to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Static discharge could act as an ignition source.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Vinyl toluene, if not stabilized, will polymerize with generation of heat. Uninhibited monomer vapors can polymerize and plug ventilation and relief devices causing dangerous pressure and vapor concentrations to build. Substance is a strong reducing agent and reacts violently with oxidants and aluminum salts.

Chemical Stability: Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

EJ-290 Part A Resin & Part B Monomer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Possibility of Hazardous Reactions: This product has been stabilized with Butylated hydroxytoluene. Product will not undergo hazardous polymerization when stored under normal conditions.

Conditions to Avoid: Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Aromatic solvents. Ketones. Aluminum chloride. Peroxides.

Hazardous Decomposition Products: Carbon dioxide (CO₂). Nitrogen oxides. Acrid smoke and irritating fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Acute Toxicity: Harmful if inhaled.

LD50/LC50 Values That Are Relevant for Classification:

EJ-290 Parts A & B	ATE (Inhalation, Vapors)	11 mg/L/4h
Vinyl Toluene (CAS# 25013-15-4)	LD50 (Oral – Rat)	4000 mg/kg
	ATE (Inhalation, Vapors)	11.00 mg/L/4h
2,5-Diphenyloxazole (CAS# 92-71-7)	ATE US (Oral)	500 mg/kg
1,4-Bis(5-phenyl-2-oxazole)benzene (CAS# 1806-34-4)	ATE US (Oral)	500 mg/kg
2,6-Dit-tert-butyl-p-cresol (CAS# 97123-41-6)	LD50 (Oral – Rat)	> 2930 mg/kg
	LD50 (Dermal – Rat)	> 2000 mg/kg

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not classified.

Carcinogenicity: Not classified.

NTP	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.		
IARC	Vinyl Toluene	CAS# 25013-15-4	Group 3
	2,6-Dit-tert-butyl-p-cresol	CAS# 97123-41-6	Group 3
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.		

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Aspiration Hazard: May be fatal if swallowed and enters airways.

EJ-290 Part A Resin & Part B Monomer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Symptoms Related to the Physical, Chemical and Toxicological Characteristics

Symptoms/Injuries After Inhalation: Harmful if inhaled. High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact: Causes skin irritation. May be absorbed through the skin in harmful amounts.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: May be fatal if swallowed and enters airways. Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None known.

Additional Information

The information presented here is to the best of our knowledge. The chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Vinyl Toluene (CAS# 25013-15-4)	
LC50 Fish 1	23.4 mg/l (Exposure time: 96 h - Species: Pimephales rafinesque)

2,6-Di-tert-butyl-p-cresol (CAS# 97123-41-6)	
EC50 Other Aquatic Organisms 2	0.43 mg/l (Exposure time: 72 h - Species: Desmodemus subspicatus)

Persistence and Degradability

EJ-290 Parts A & B	
Persistence and Degradability	Not established.

Bioaccumulative Potential

EJ-290 Parts A & B	
Bioaccumulative Potential	Not established.

Vinyl Toluene (CAS# 25013-15-4)	
BCF Fish 1	32 – 35
Log Pow	3.36

2,6-Di-tert-butyl-p-cresol (CAS# 97123-41-6)	
BCF Fish 1	230 - 2500
Log Pow	4.17

Mobility in Soil

Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

EJ-290 Part A Resin & Part B Monomer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology – Waste Materials: Hazardous waste due to toxicity.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT

UN Number : 2618
UN Proper Shipping Name : VINYL TOLUENES, STABILIZED
Transport Hazard Class : 3
Packing Group : III
Label Codes : 3
ERG Number : 130P
Marine Pollutant : Marine pollutant

In Accordance with IMDG

UN Number : 2618
UN Proper Shipping Name : VINYL TOLUENES, STABILIZED
Transport Hazard Class : 3
Packing Group : III
Label Codes : 3
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D
Marine Pollutant : Marine pollutant

In Accordance with IATA

UN Number : 2618
UN Proper Shipping Name : VINYL TOLUENES, STABILIZED
Transport Hazard Class : 3
Packing Group : III
Label Codes : 3
ERG Code (IATA) : 3L

In Accordance with TDG

UN Number : 2618
UN Proper Shipping Name : VINYL TOLUENES, STABILIZED
Transport Hazard Class : 3
Packing Group : III
Label Codes : 3
Marine Pollutant (TDG) : Marine pollutant

EJ-290 Part A Resin & Part B Monomer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 15: REGULATORY INFORMATION

Safety, Health, and Environmental Regulations Specific for the Substance or Mixture

US Federal Regulations



TSCA Inventory	The following components are listed: Vinyl toluene (CAS# 25013-15-4) 2,5-Diphenyloxazole (CAS# 92-71-7) 1,4-Bis(5-phenyl-2-oxazole)benzene (CAS# 1806-34-4) 2,6-Dit-tert-butyl-p-cresol (CAS# 97123-41-6)	
EPA TSCA Regulatory Flag	Vinyl toluene (CAS# 25013-15-4)	T – A substance that is the subject of a Section 4 test rule under TSCA.
SARA 311/312 Hazards	Fire hazard, Acute health hazard	

US State Regulations

Vinyl toluene (CAS# 25013-15-4)
U.S. – Massachusetts – Right to Know List
U.S. – New Jersey – Right to Know List
U.S. – Pennsylvania – Right to Know List

2,6-Dit-tert-butyl-p-cresol (CAS# 97123-41-6)
U.S. – Massachusetts – Right to Know List
U.S. – New Jersey – Right to Know List
U.S. – Pennsylvania – Right to Know List

Canadian Regulations

EJ-290 Parts A & B	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
 	

Vinyl toluene (CAS# 25013-15-4)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

2,5-Diphenyloxazole (CAS# 92-71-7)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EJ-290 Part A Resin & Part B Monomer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

1,4-Bis(5-phenyl-2-oxazole)benzene (CAS# 1806-34-4)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

2,6-Di-tert-butyl-p-cresol (CAS# 97123-41-6)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION

Date of Issue: 5/13/2015

Revision Date: 5/13/2016

Other Information: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Abbreviations Used in Section 3:

Acute Tox. 4 (Inhalation: vapor)	Acute Toxicity, Inhalation:vapor, Category 4
Acute Tox. 4 (Oral)	Acute Toxicity, Oral, Category 4
Aquatic Acute 1	Hazardous to the Aquatic Environment – Acute Hazard, Category 1
Aquatic Acute 3	Hazardous to the Aquatic Environment – Acute Hazard, Category 3
Aquatic Chronic 1	Hazardous to the Aquatic Environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment – Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the Aquatic Environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration Hazard, Category 1
Eye Irrit. 2A	Serious Eye Damage/Eye Irritation, Category 2A
Flam. Liq. 3	Flammable Liquids, Category 3
Skin Irrit. 2	Skin Corrosion/Irritation, Category 2
H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Party Responsible for the Preparation of This Document:

Eljen Technology (325) 235-4276

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.