

SECTION 1: IDENTIFICATION**Product Identifier****Product Name:** EJ-520 Reflective Paint – Part A**Product Form:** Mixture**Intended Use of the Product**

Reflective coating.

Name, Address, and Telephone of the Responsible Party

Company/Manufacturer: Eljen Technology
Address: 1300 W. Broadway
SWEETWATER, TEXAS 79556
USA
Phone: (325) 235-4276
Fax: (325) 235-0701
Website: www.eljentechnology.com

Emergency Telephone Number

Emergency Number: CHEMTREC (24 hours)
(800) 424-9300

SECTION 2: HAZARDS IDENTIFICATION**Classification of the Substance or Mixture****Classification (GHS-US):**

Flammable liquid, Category 3	H226
Germ cell mutagenicity, Category 1B	H340
Carcinogenicity, Category 1B	H350
STOT-RE, Category 2	H373

Label Elements**GHS-US Labeling:****Hazard Pictograms (GHS-US):**

Signal Word (GHS-US): Danger

Hazard Statements (GHS-US):

H226	Flammable liquid and vapor.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to the hearing organs through prolonged or repeated exposure.

Precautionary Statements (GHS-US):

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.
P233	Keep container tightly closed.

EJ-520 Reflective Paint – Part A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P240	Ground/Bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe vapors, mist, or spray.
P280	Wear protective gloves, protective clothing, and eye protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P370 + P378	In case of fire: Use appropriate media (see section 5 on SDS) to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with all local, regional, national, provincial, territorial, and international regulations.

Hazards Not Otherwise Classified

Not applicable.

Components With Unknown Acute Toxicity (GHS-US)

Not applicable.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Hazardous Components:

Any hazardous components not listed below are not present in quantities requiring disclosure.

Name	Product Identifier	Concentration (%)
2-methoxy-1-methylethyl acetate	CAS# 108-65-6	53.985
Xylene	CAS# 1330-20-7	2.25
Solvent naphtha (petroleum), light arom.	CAS# 64742-95-6	1.97
Ethylbenzene	CAS# 100-41-4	1.64
m-Xylene	CAS# 108-38-3	1.26
1,2,4-trimethylbenzene	CAS# 95-63-6	0.22

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If exposed or concerned, get medical advice/attention.

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or a doctor if you feel unwell.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Seek medical attention immediately if skin irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if eye irritation develops or persists.

Ingestion: Rinse mouth. Do not induce vomiting. Immediately call a poison center or a doctor.

Most Important Symptoms and Effects, Both Acute and Delayed

Inhalation: May cause irritation to upper respiratory tract. Symptoms may include dizziness, narcosis, nausea, dryness of throat.

EJ-520 Reflective Paint – Part A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Skin Contact: May cause skin irritation. Symptoms may include drying, cracking or flaking of skin. Prolonged exposure may cause redness and swelling which may lead to dermatitis.

Eye Contact: May cause eye irritation. Symptoms may include pain, tearing and swelling of the eyes. Prolonged exposure may cause conjunctivitis.

Ingestion: May cause irritation of the digestive tract. Symptoms may include diarrhea, vomiting, sore throat, and nausea.

Chronic Symptoms: May cause genetic defects. May cause cancer. May cause damage to the hearing organs through prolonged or repeated exposure.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If any of the above symptoms are present and persist, seek immediate medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Agents: Carbon dioxide, sand, extinguishing powder. Do not use water, especially water with full jet since it may spread fire.

Special Hazards Arising from the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: Product is not explosive, but formation of explosive air/vapor mixtures is possible.

Reactivity: Hazardous reactions will not occur under recommended storage and handling conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting instructions: In case of major fire and large quantities, evacuate area. Fight fire remotely due to the risk of explosion. Do not allow run-off from firefighting to enter drains or water courses. Do not breathe fumes from fires or vapors from decomposition.

Protection During Firefighting: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Hazardous Combustion Products: None known.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static charges. Keep away from heat, sparks, open flames, hot surfaces. No smoking. Do NOT breathe vapor, mist, or spray.

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Ventilate area. Eliminate ignition sources. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters.

EJ-520 Reflective Paint – Part A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Absorb with liquid-binding material such as sand, diatomite, acid binders, or universal binders. Dispose contaminated material in the same manner as waste product. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents.

Reference to Other Sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Hygiene Measures: Do not breathe vapors, mist or spray. Wash hands and other exposed areas thoroughly with soap and water after handling. Do not eat, drink or smoke when using this product. Wear personal protective equipment as recommended in section 8.

Technical Measures: Keep product away from heat, sparks, open flames, and hot surfaces. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical, ventilating, and/or lighting equipment. Use only with mechanical exhaust ventilation.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Follow proper grounding procedures to avoid static discharge. Ground or bond container and receiving equipment.

Storage Conditions: Store in a cool, dry, well-ventilated place. Keep container tightly closed when not in use. Store locked up. Keep in a fireproof place. Keep away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong oxidizers. Phosphorus-containing materials.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or appropriate advisory agency.

Components with Workplace Control Parameters:

2-methoxy-1-methylethyl acetate (CAS# 108-65-6)	AIHA (WEEL)	50 ppm TWA
Xylene (CAS# 1330-20-7)	OSHA (PEL)	435 mg/m ³ (100 ppm) TWA
	ACGIH (TLV)	434 mg/m ³ (100 ppm) TWA 651 mg/m ³ (150 ppm) STEL
	ACGIH (BEI)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
	NIOSH (REL)	435 mg/m ³ (100 ppm) TWA 655 mg/m ³ (150 ppm) STEL
Ethylbenzene (CAS# 100-41-4)	OSHA (PEL)	435 mg/m ³ (100 ppm) TWA
	ACGIH (TLV)	87 mg/m ³ (20 ppm) TWA
	ACGIH (BEI)	0.7 g/g creatinine

EJ-520 Reflective Paint – Part A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

		<p>Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)</p> <p>Medium: end-exhaled air Time: not-critical Parameter: Ethyl benzene (semi-quantitative)</p>
	NIOSH (REL)	<p>435 mg/m³ (100 ppm) TWA 545 mg/m³ (125 ppm) STEL</p>
m-Xylene (CAS# 108-38-3)	OSHA (PEL)	435 mg/m ³ (100 ppm) TWA
	ACGIH (TLV)	<p>434 mg/m³ (100 ppm) TWA 651 mg/m³ (150 ppm) STEL</p>
	ACGIH (BEI)	<p>1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids</p>
	NIOSH (REL)	<p>435 mg/m³ (100 ppm) TWA 545 mg/m³ (125 ppm) STEL</p>

Exposure Controls

Appropriate Engineering Controls: Where eye contact can occur, have eye washing facilities readily available. Use only with mechanical exhaust ventilation. Ensure adequate ventilation, especially in confined areas. Follow proper grounding procedures to avoid static discharge. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Gas detectors should be used when flammable vapors may be released.

Personal Protective Equipment

Eye/Face Protection: Wear chemically resistant safety goggles.

Skin and Body Protection: Wear chemically resistant protective gloves. Wear suitable protective clothing made from chemically and fire resistant/ flame retardant materials and fabrics.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Appearance	: White liquid
Odor	: Solvent-like
Odor Threshold	: No data available
pH	: No data available
Melting Point/Freezing Point	: No data available
Boiling Point/Boiling Range	: 146°C (295°F)
Flash Point	: 44°C (111°F)
Evaporation Rate	: No data available
Flammability (solid, gas)	: Not applicable
Lower Flammability/Explosion Limit	: 1.5%
Upper Flammability/Explosion Limit	: 10.8%
Vapor Pressure	: 3.4 hPa (3 mm Hg) at 20°C (68°F)
Vapor Density	: No data available
Relative Density	: No data available
Density	: 1.02 g/cm ³ at 20°C (68°F)

EJ-520 Reflective Paint – Part A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Solubility	: Miscible in water
Partition Coefficient (n-octanal/water)	: No data available
Ignition Temperature	: 315°C (599°F)
Auto Igniting	: Product is not self-igniting
Decomposition Temperature	: No data available
Viscosity	: No data available
Percent Volatile by Volume	: 63.2%

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under recommended storage and handling conditions.

Chemical Stability: Flammable liquid. Product is not explosive, but formation of explosive air/vapor mixtures is possible. Product is stable under recommended storage and handling conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: High temperatures, heat, hot surfaces, sparks, open flames, and other ignition sources.

Incompatible Materials: Strong oxidizers. Phosphorus-containing materials.

Hazardous Decomposition Products: Carbon dioxide. Carbon monoxide. Oxides of nitrogen.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Acute Toxicity: Not classified.

LD50/LC50 Values That Are Relevant for Classification:

Solvent naphtha (petroleum), light arom. (CAS# 64742-95-6)	LD50 (Oral – Rat)	> 6800 mg/kg
	LD50 (Dermal – Rabbit)	> 3400 mg/kg
	LC50 (Inhalation – Rat)	> 10.2 mg/l/4h

Skin Corrosion/Irritation: Not classified.

Serious Eye Damage/Irritation: Not classified.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: May cause genetic defects.

Carcinogenicity: May cause cancer.

NTP	Cumene	CAS# 98-82-8	Group R
IARC	Xylene	CAS# 1330-20-7	Group 3
	Ethylbenzene	CAS# 100-41-4	Group 2B
	m-Xylene	CAS# 108-38-3	Group 3
	p-Xylene	CAS# 106-42-3	Group 3
	o-Xylene	CAS# 95-47-6	Group 3
	2-Butoxyethanol	CAS# 111-76-2	Group 3
	Cumene	CAS# 98-82-8	Group 2B
	Toluene	CAS# 108-88-3	Group 3
OSHA	No component of this product present at levels greater than or equal to 0.1%		

EJ-520 Reflective Paint – Part A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

is identified as a probable, possible or confirmed human carcinogen by OSHA.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to the hearing organs through prolonged or repeated exposure.

Aspiration Hazard: Not classified.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics

Symptoms/Injuries After Inhalation: May cause irritation to upper respiratory tract. Symptoms may include dizziness, narcosis, nausea, dryness of throat.

Symptoms/Injuries After Skin Contact: May cause skin irritation. Symptoms may include drying, cracking or flaking of skin. Prolonged exposure may cause redness and swelling which may lead to dermatitis.

Symptoms/Injuries After Eye Contact: May cause eye irritation. Symptoms may include pain, tearing and swelling of the eyes. Prolonged exposure may cause conjunctivitis.

Symptoms/Injuries After Ingestion: May cause irritation of the digestive tract. Symptoms may include diarrhea, vomiting, sore throat, and nausea.

Chronic Symptoms: May cause genetic defects. May cause cancer. May cause damage to the hearing organs through prolonged or repeated exposure.

Additional Information

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: ECOLOGICAL INFORMATION

Avoid release to the environment. Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial, and international regulations.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT

UN Number	: 1263
UN Proper Shipping Name	: Paint
Transport Hazard Class	: 3
Packing Group	: III
Label Codes	: 3
Marine Pollutant	: No

EJ-520 Reflective Paint – Part A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

In Accordance with IMDG

UN Number : 1263
UN Proper Shipping Name : PAINT
Transport Hazard Class : 3
Packing Group : III
Label Codes : 3
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Marine Pollutant : No

In Accordance with IATA

UN Number : 1263
UN Proper Shipping Name : PAINT
Transport Hazard Class : 3
Packing Group : III
Label Codes : 3

SECTION 15: REGULATORY INFORMATION

Safety, Health, and Environmental Regulations Specific for the Substance or Mixture

US Federal Regulations

TSCA Inventory	All components are listed.
SARA 313 Components	The following components are subject to reporting levels established by SARA Title III, Section 313: Xylene (CAS# 1330-20-7) Ethylbenzene (CAS# 100-41-4) m-Xylene (CAS# 108-38-3) p-Xylene (CAS# 106-42-3) o-Xylene (CAS# 95-47-6) 1,2,4-Trimethylbenzene (CAS# 95-63-6) 2-Butoxyethanol (CAS# 111-76-2) Cumene (CAS# 98-82-8) Toluene (CAS# 108-88-3)

US State Regulations

U.S. – California – Proposition 65 – Carcinogens List	The following components are listed: Ethylbenzene (CAS# 100-41-4) Cumene (CAS# 98-82-8)
U.S. – California – Proposition 65 – Female Reproductive Toxin List	The following components are listed: Toluene (CAS# 108-88-3)
U.S. – California – Proposition 65 – Developmental Toxin List	The following components are listed: Toluene (CAS# 108-88-3)

NFPA Rating

Health : 0
Fire : 2
Reactivity : 0

HMIS Rating

Health : *0
Flammability : 2
Reactivity : 0

EJ-520 Reflective Paint – Part A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 16: OTHER INFORMATION

Date of Issue: 6/25/2015

Revision Date: 7/13/2016

Other Information: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document:

Eljen Technology (325) 235-4276

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.